

Mosa. Declaration of performance

No. VTO-01-1307-01

2. Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, type 1, with water absorption $E_p \leq 0,5\%$

3. Intended use(s)
For internal and external walls and floorings

4. Name or registered trade mark, and contact address of the manufacturer
Koninklijke Mosa B.V., Meerssenerweg 358 NL 6224 AL Maastricht

6. System(s) of assessment and verification of constancy of performance (AVCP)
System 4

7. Name and identification number of notified laboratory, if relevant

Task(s) carried out

AVCP system

Document issued and date of issue

9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 1600 N	
Slipperiness		
- CEN/TS 16165:2011 annex A	$\geq R9$	
- CEN/TS 16165: 2011 annex C	≥ 39	
Tactility	NPD	
Bond strength/adhesion, for:		
- Cementitious adhesive, type C2	$\geq 1,0$ N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- Internal use:	Pass	
- External use: freeze-thaw resistance	Pass	

10. The performance of the product identified in point 2 is in conformity with the declared performances in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A. Thomaes, CEO

Name and function

Maastricht, 28-06-2013

Place and date of issue

Signature

