

# Mosa. Declaration of performance

## No. WTG-01-1307-01

2. Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, type 1, with water absorption  $E_w > 10\%$**

3. Intended use(s)  
**For internal walls**

4. Name or registered trade mark, and contact address of the manufacturer  
**Koninklijke Mosa B.V., Meerssenerweg 358 NL 6224 AL Maastricht**

6. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**

7. Name and identification number of notified laboratory, if relevant

Task(s) carried out

AVCP system

Document issued and date of issue

9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	<b>A1</b>	<b>EN 14411:2012</b>
<b>Release of dangerous substance, for:</b>		
- Cadmium	<b>NPD</b>	
- Lead	<b>NPD</b>	
<b>Breaking strength</b>		
- < 7,5 mm	<b>≥ 300 N</b>	
- ≥ 7,5 mm	<b>≥ 900 N</b>	
<b>Slipperiness</b>	<b>NPD</b>	
<b>Tactility</b>	<b>NPD</b>	
<b>Bond strength/adhesion, for:</b>		
- Cementitious adhesive, type C1	<b>≥ 0,5 N/mm<sup>2</sup></b>	
<b>Thermal shock resistance</b>	<b>Pass</b>	
<b>Durability for:</b>		
- Internal use:	<b>Pass</b>	

10. The performance of the product identified in point 2 is in conformity with the declared performances in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

R. Veraart, CEO

Name and function

Maastricht, 28-06-2013

Place and date of issue

Signature

