

## Declaration of performance No. VTO-01-1307-01

2. Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, type 1, with water absorption  $E_p \leq 0.5\%$**

3. Intended use(s)  
**For internal and external walls and floorings**

4. Name or registered trade mark, and contact address of the manufacturer  
**Koninklijke Mosa bv, Meerssenerweg 358 NL-6224 AL Maastricht**

6. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**

7. Name and identification number of notified laboratory, if relevant:

Task(s) carried out:

AVCP system:

Document issued and date of issue:

9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	<b>A1<sub>FL</sub>/A1</b>	<b>EN 14411</b>
<b>Release of dangerous substance for:</b>		
- Cadmium	<b>NPD</b>	
- Lead	<b>NPD</b>	
<b>Breaking strength</b>	<b><math>\geq 1600</math> N</b>	
<b>Slipperiness:</b>		
- CEN/TS 16165:2011 annex A	<b><math>\geq R9</math></b>	
- CEN/TS 16165:2011 annex C	<b><math>\geq 39</math></b>	
<b>Tactility</b>	<b>NPD</b>	
<b>Bond strength / adhesion for:</b>		
- Cementitious adhesive, type C2	<b><math>\geq 1.0</math> N/mm<sup>2</sup></b>	
<b>Thermal shock resistance</b>	<b>Pass</b>	
<b>Durability for:</b>		
- Internal use	<b>Pass</b>	
- External use: freeze-thaw resistance	<b>Pass</b>	

10. The performance of the product identified in point 2 is in conformity with the declared performances in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A. Thomaes, CEO

Name and function

Maastricht, 28-06-2013

Place and date of issue



Signature