

Declaration of performance No. WTG-01-1307-01

2. Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, type 1, with water absorption $E_w > 10\%$

3. Intended use(s)
For internal walls

4. Name or registered trade mark, and contact address of the manufacturer
Koninklijke Mosa bv, Meerssenerweg 358 NL-6224 AL Maastricht

6. System(s) of assessment and verification of constancy of performance (AVCP)
System 4

7. Name and identification number of notified laboratory, if relevant:

Task(s) carried out:

AVCP system:

Document issued and date of issue:

9. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411
Release of dangerous substance for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength:		
- < 7.5 mm	≥ 300 N	
- ≥ 7.5 mm	≥ 900 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength / adhesion for:		
- Cementitious adhesive, type C1	≥ 0.5 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- Internal use	Pass	

10. The performance of the product identified in point 2 is in conformity with the declared performances in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.


Signed for and on behalf of the manufacturer by:

A. Thomaes, CEO

Name and function

Maastricht, 28-06-2013

Place and date of issue



Signature