

## Declaration of performance wall tiles, WTG-01-1307-01

1. Type, batch or serial number or any other element allowing identification of the product  
**Dry-pressed ceramic tiles, type 1, with water absorption Eb > 10%**

2. Intended use(s)  
**For internal walls**

3. Name or registered trade mark, and contact address of the manufacturer  
**Koninklijke Mosa bv, Meerssenerweg 358 NL-6224 AL Maastricht, made in the Netherlands,**

4. System(s) of assessment and verification of constancy of performance (AVCP)  
**System 4**

5. Declared performances

Essential characteristics	Performance	Technical specification
<b>Reaction to fire</b>	<b>A1</b>	<b>EN 14411:2016</b>
<b>Release of dangerous substance for:</b>		
- Cadmium	<b>NPD</b>	
- Lead	<b>NPD</b>	
<b>Breaking strength</b>		
- < 7.5 mm	<b>≥ 300 N</b>	
- ≥ 7.5 mm	<b>≥ 900 N</b>	
<b>Slipperiness</b>	<b>NPD</b>	
<b>Tactility</b>	<b>NPD</b>	
<b>Bond strength / adhesion for</b>		
- Cementitious adhesive, type C1	<b>≥ 0.5 N/mm<sup>2</sup></b>	
<b>Thermal shock resistance</b>	<b>Pass</b>	
<b>Durability for:</b>		
- Internal use	<b>Pass</b>	


6. The performance of the product identified in point 1 is in conformity with the declared performances in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Willem Stas - COO  
Name and function

Maastricht, 17-04-2023  
Place and date of issue

  
Signature